



Available only from the technology experts at SMART PARK

- **Designed for Commercial and Industrial Applications**
- **3 Switchable Viewing Angles.**
- **Calibrated to suit a full range of mounting heights**
- **High Resolution Megapixel Imager**
- **Heavy Duty Metal Waterproof Housing**
- **Camera with inbuilt Microphone**
- **Very High Dynamic Range Imager for high contrast environments.**
- **Three Year Warranty**
- **Hibrite LED lighting for great low light performance in all conditions.**
- **Using the highest quality OEM grade components for reliability and durability.**

Specifications	CAM150MV
Dimension (mm)	82 (L) x 73 (W) x 58 (D) mm
Image Sensor	1/2.7" OV10635 Digital
Lens	Focal Length 1.78mm Max Aperture F2.0
View angle (Horizontal)	180°
View angle (Vertical)	190
IR LED	Yes (On/Off)
Microphone	Yes
Power Requirements	DC 12V
Power consumption	1.2W
Mirror control	Yes
Video format	NTSC
Video signal output	1 Vp-p (75ohm)
Effective Pixel Resolution	NTSC 720 x 480
S/N (dB)	<39 Db
Illumination (min.)	0 Lux With IR LED (ON/OFF)
Additional Specifications	Automatic Exposure/Gain Control
Self diagnostic controller	Auto White Balance
	Aperture & Gamma Correction
Waterproof and dustproof	IP69K
Operating Temperature Range	-30°C ~ +85 °C RH95% Max
Storage temperature	-40°C~+105°C RH95% Max
Weight	(Including Mounting Bracket)144g
Guide Line	Yes